



















Contact

Address: - 10, Malhar Industrial Park, Behind Safari Hotel, Nr. Odhav Ring Road

circle, S. P. Ring Road, Ahmedabad - 382 415

Mobile:-Rajesh Mewada +91-81692-51338/ +91-93200-72464

Mobile:-Amit Mewada +91-93279-01122

E-mail:- aryanrubber@yahoo.com website:- www.aryanrubberproducts.com



Company Profile

ARYAN RUBBER PRODUCTS represents desire to achieve customers Satisfaction through hard, dedicated and quality work; in our case, in the Field of rubber products.

ARYAN RUBBER PRODUCTS was started as a manufacturer for rubber items in the year 2008. We are counted amongst one of the leading manufacturers of rubber products, out of various compounds like NATURAL, NITRILE, EPDM, NEOPRENE, HYPOLENE, SILICON, VITON and POLYURETHANE RUBBER.

Quality is the backbone of any well known company. Through our continuous efforts and sense of customer satisfaction we are always confident in developing complicated items including import substitutes. We have earned customer confidence by understanding their expectations and fulfilling them.

ARYAN RUBBER PRODUCTS has specialized in development, research and production of items which are being used in various industries, using high profile devices for pneumatic and hydraulic systems. We are the manufacturers of high tensile rubber items as per customer's specification with excellent heat resistance water proof and wear resistance. The material used is exactly as per the specifications after ascertaining the exact application. Raw material undergoes thorough inspection in our laboratory before use in manufacturing.



We Deserve To Serve You

Technical Specification:

MATERIAL	TEM RESISTANT	OIL RESISTANT	ABRASSION	OZONE	TENSILE STRENGT H (PSI)	ELONG -ATION	TEAR RESISTANT
NATURAL RUBBER(NR)	85 DEG.	85 DEG.	FAIR	POOR	4500	600- 800%	GOOD
SYNTHETIC RUBBER(IR)	85 DEG.	FAIR	FAIR	FAIR	4500	600%	GOOD
POLYBUTADIN RUBBER(BR)	70 DEG	FAIR	EXCELLENT	FAIR	POOR- FAIR	POOR- FAIR	LOW POOR
STYDENE BUTADINE RUBBER(SBR)	80 DEG	FAIR	GOOD	FAIR	3000-4000	500- 600%	EXCELLENT
NEOPRENE(CR)	95 DEG	EXCELLENT	GOOD	GOOD	4000	800%	GOOD
NITRIL RUBBER(NBR)BUTADINE ACRYLO NITRIL RUBBER	100 DEG	EXCELLENT	EXCELLENT	GOOD	2500	550%	FAIR
EPDM ETHYLENE PROPLENE DIENE	140 DEG	POOR	EXCELLENT	EXCELLENT	3000	500- 600%	EXCELLENT
FKM(VITON)	250 DEG	EXCELLENT	GOOD	EXCELLENT	1500-2000	600%	POOR
SILICON (MVQ)	>150 DEG	GOOD	POOR	EXCELLENT	1500	600%	POOR
BOTYL RUBBER (IIR)	100 DEG	POOR	FAIR	GOOD	3000	400%	EXCELLENT
HYPALON RUBBER(SM)	150 DEG	GOOD	EXCELLENT	EXCELLENT	3000	300- 500%	FAIR

'O' Ring



Size

Material

2mm ID to 2000mm ID, hickness 1 mm to 25 mm, More than 5000 Sizes Nitrile, Neoprene, Silicon, Viton, EPDM,P-U & Fiber, PTFE

Oil seal

Size	Ma
10mm OD to 1100 mm OD,	Nitrile, Neo
More than 200 Sizes	Viton, EPDN

Material e, Neoprene, Silicon,



Hydraulic/Pneumatic Seal



Material

10mm OD to 1100 mm OD, More than 2000 Sizes Polyurethane, Butyl, Filled PTFE,NBR, Nylon with Reinforced Rubber

Gasket



Size	Material
20 mm to 1000mm Available in various	Natural , Synthetic Neoprene, Silicon, EPDM,
thickness, More than 1000 size	Viton, PTFE, Asbestos, Non-Asbestos & Spiral wound Gasket

Grommet

Size	Material
20 mm to 1000mm	Natural , Synthetic
Available in various	Neoprene, Silicon, EPDM,
thickness,	Viton, PTFE, Asbestos,
More than 1000 size	Non-Asbestos &
	Spiral wound Gasket




Rubber Sheet



Size	Material
Thickness 0.2 to 40mm	Natural , Neoprene,
1500 W to 2000mm L long	Silicon, EPDM,
length	Viton, & Sponge Rubber

Diaphragm



Size	Material
20 mm to 600mm for different applications	Natural , Neoprene, Silicon, EPDM, Viton, PTFE etc.



Rubber Bush / Coupling Bush

Size	Material
More than 500 Sizes	Natural , Neoprene, Nitril, Canvas, Viton, Reinforced with Rubber, Nylon, PTFE.





Rubber Coupling





Size	
	Natur
lifferent applications	Impet
	4.1

Natural, Nitril, Fiber, Impetrated With or without metal fitting

Material

Tire Coupling



Size Material More than 75 Sizes foe power Transmission, Generators. Natural, Neoprene, Nitril, fiber Impetrated.

Star Coupling

Size	Material
More than 50 varieties	Natural , Neoprene, Silicon, P-U





Anti Vibration pad / Mountings





Size		
More than 150 sizes &		
verities		
More than 50 verities		

Natural, Nitrile, With or without metal fitting.

Material

Rubber Cord



Size Material

.0 mm Dia to 50 mm Dia Natural, Neoprene,

Natural , Neoprene, Silicon, silicon, Viton, sponge , PTFE, Polyurethane

Rubber Strip

Size	Material
More than 10000 Sizes	NBR, EPDM, Silicone, Viton, Strong EPDM, Capsul, foam strip





Tubes / Rubber Sleeve



Size	Material
Id-4 mm to 75 mm more than 1000 sizes	Natural , Neoprene, NBR, Viton, silicon, polyurethane, PTEF

Metal Bonded Parts



Size Material

More than 200 verities Natural , Neoprene, Nitril , silicon, viton

Victaulic coupling

Size	Material
15mm to 150 mm	Casting –SGI / S.S Bush – Neoprene, Nitril ,Etc



PTFE Parts



Size	Material
More than 1000 sizes & verities for Hydraulic , Pneumatics valves	Pure PTFE , BFT, CFT & (MOS2)

Expansion Bellows



Size	Material
1" NB to 72" NB with hydro	Neoprene, EPDM,
testing up to 24 bar	Silicon, Viton , Natural
pressure	rubber

Protection Bellows

Size	Material
Round, Square,	Nylon Fabric coated With,
Rectangular, octagonal,	Polyurethane, High
Odd shapes	Tensile polyimide fabric,
	canvas, leather, Nylon
	Fabric with Rubber



Castors



Size	Material
More than 200 sizes with different fitting	Polyurethane, Rubber Nylon MS/SS Castors